

Specifications	PBS16-C1	PBS16-C2	
Tail configuration	Connection terminal(1.8X0.4)	Connection terminal(1.8X0.4)	
Switch specifications	3A/250VAC	3A/250VAC	
Contact resistance	≤50mΩ	≤50mΩ	
Insulation resistance	≥1000MΩ	≥1000MΩ	
Dielectric Intensity	2000VAC	2000VAC	
Ambient temperature	-20°C~+55°C	-20°C~+55°C	
Mechanical life	500,000 cycles	500,000 cycles	
Electrical life	50,000 cycles	50,000 cycles	
Panel thickness	1~15mm	1~15mm	
Nut torque	5~14Nm	5~14Nm	
Operation pressure	About 3-5N	About 3-5N	
Operation stroke	About 2.8mm	About 2.8mm	
Protection level	IP67,IK10	IP67,IK10	
Contact	Silver alloy	Silver alloy	
Button	Nickel plated brass/stainless stell	Nickel plated brass/stainless stell	
Enclosure	Nickel plated brass/stainless stell	Nickel plated brass/stainless stell	
Base	PBT	PBT	
LED type	Ring illuminated(LED)	Ring illuminated(LED)	
Rated voltage	6V/12V/24V/110V/220V	6V/12V/24V/110V/220V	
LED color	R O Y G B W	R O Y G B W	
LED life	40000hours	40000hours	